



Bosch BP Heat Pump

Best-in-class efficiency and lower operating costs, providing the ultimate value for your money





Bosch BP Model

The Greensource i Series BP Model geothermal heat pump comes in a horizontal or vertical configuration. This packaged solution can individually replace your old system or be used for a new installation. The BP model comes equipped with the quality and innovative technology that only Bosch can provide.

Features

- Single-stage rotary (sizes 012, 018) and scroll (sizes 024-048) compressors
- Available in 1 through 4 tons
- ▶ PSC motor standard on size 012 only
- **ECM** motors standard for sizes 018, 024, 030, 036, 042, 048
- Mid-range performance and low operation costs
- Environmentally friendly R410-A refrigerant
- ▶ White pre-painted sheet metal cabinet for durability & look
- ▶ Quiet operation 1/2" 1.5lb. Dual Density Fiberglass Insulation
- ► Electronic circuit board with alert LED display which can also display fault information on the thermostat
- Evaporator Coil Tin-plated copper tubing hair pins with high-tech polymer coated Aluminum Fins for durability & reliability



Why Bosch Geothermal Heat Pumps?

Being Green Means Saving Green

This fully featured single-stage heat pump offers an appliance-style cabinet in sizes of 1 to 4 tons. The Bosch Greensource geothermal heat pump requires less energy to produce the equivalent cooling and heating output of other conventional heat pumps on the market. This saves energy and reduces the cost to stay comfortable in your home. You can save up to 65% on your energy bills, plus payback on this investment can be as short as 5 to 7 years.

Reliable and High Quality

Bosch's Unit Protection Module (UPM) aids in troubleshooting and helps reduce the time required to diagnose the operation of the unit in order to keep it running at optimal conditions. The UPM circuit board can send automatic alerts to be displayed on a Bosch thermostat therefore expediting any maintenance that is required.

Quiet Operation

Greensource is equipped with an advanced sound package comprising of a unique floating base pan to isolate internal components from the exterior cabinet thereby reducing sound and vibration. Combined with dual density fiberglass cabinet insulation makes the Greensource one of the quietest units on the market.

30% Geothermal Tax Credit

Being Green Means Saving Green

Homeowners who install Bosch ENERGY STAR qualified geothermal heat pumps are eligible for a 30% tax credit, including the cost of installation for systems placed in service by $1/1/2033^*$, a 26% tax credit for systems placed in service after 12/31/2032 and before 01/01/2034, and a 22% tax credit for systems placed in service after 12/31/2033 and before 01/01/2035. All tax credits are on the cost of the geothermal system, including installation costs.

Additionally, many areas offer local incentives for utilities, counties, or states. Visit the DOE's "Database of State Incentives for Renewable Energy" (DSIRE) at dsireusa.org to find out just what is in store for you!



BP Model Features

Cabinet

Cabinetry is constructed using white pre-painted, galvanized steel for a sleek appliance aesthetic.

Quiet Operation

All panels are insulated with ½" thick, 1.5 lb./cu.ft. density micromat fiberglass insulation for both thermal insulation and noise reduction thereby keeping your home quieter and temperature regulated.

Serviceability

- ▶ Designed to be serviced from the front of the unit.
- Insulated bulkheads allow the unit to be serviced during operation.

High Efficiency Motors

- ▶ PSC (standard) for size 012
- ► ECM Constant Torque (standard) for sizes 018-048

Hanging Brackets for Easy Installation

All horizontal (HZ) units come standard with hanging bracket kits for suspending the unit from field supplied hanger rods.

Quality Water Connections

All water connections are heavy duty bronze FPT fittings securely fastened to the unit corner post.

Refrigerant Circuit

Designed using the optimum combination of compressor, water and copper tin plate and aluminum fin evaporator coils with TXV to provide peak performance and improved efficiency.

TXV (Thermal Expansion Valve)

Improves refrigerant management and efficiencies.

Superior Warranty

10 Year Limited Parts & Labor Warranty⁽¹⁾

Improved Air Filtration with 4 Sided Filter Rack & 2" MERV-8 Filter

Allows you to change your filter easily and improve your home's indoor air quality by removing 80% of airborne particles and other allergens as small as 1 micron.



DuoGuard™ Air Coil

Tin electro-plated copper tubing with high-tech polymer coated aluminum fins will protect the evaporator coil from all forms of corrosive elements in the air-stream.

Intuitive Alerts and Protection via the Electronic Circuit Board

- ► Low pressure switch protection
- ► High pressure switch protection
- Alarm output
- Condensate overflow protection
- Anti-short cycling
- ▶ 5 minute delay low pressure bypass at start up
- Random start of unit
- ▶ Brown out protection
- Evaporator freeze protection
- Water coil/coaxial coil/condenser freeze protection

BP MODELS											
SIZE	CABINET CONFIGURATION	COAX	RETURN AIR	PART NUMBER							
012		С	L	7735034028							
012	HZ		R	7735059015							
018			L	7735069605							
018		С	R	7735071213							
018	HZ		L	7735070779							
018		N	R	7735070780							
018		С	L	7735070781							
018			R	7735070005							
018	VT		L	7735070782							
018		N	R	7735070176							
024			L	7735050138							
024	HZ	С	R	7735058025							
024			L	7735030746							
024	VT	С	R	7735030412							
030			L	7735045120							
030	HZ	N	R	7735039297							
030			L	7735032070							
030		С	R	7735051681							
030	VT	N	L	7735035382							
030			R	7735030884							
036		С	L	7735051680							
036			R	7735034921							
036	HZ		L	7735037439							
036		N	R	7735036361							
036		0	L	7735041458							
036	VT	С	R	7735055608							
036	VI	N.	L	7735032549							
036		N	R	7735032551							
042	HZ	N	L	7735037449							
042	112	IN	R	7735033945							
042		С	L	7735030747							
042	VT		R	7735051683							
042	V I	N	L	7735030704							
042		1 4	R	7735034127							
048	HZ	N	L	7735040032							
048	112	1.4	R	7735039812							
048		С	L	7735037627							
048	VT		R	7735055609							
048	V I	N	L	7735028878							
048		14	R	7735030885							

Optional Features

Field Install Internal Electric Heat Kit

The field installed internal electric heat kit includes 5, 10, 15, or 20 kilowatt back up or an emergency heater that can be used depending on the size of the geothermal pump.

Field Install SmartStart Assist Kit

This device reduces starting (inrush) current for compressors by 45% to 65%, minimizing "light flickering" during compressor starts and extending the life of the compressor. Designed for single phase scroll compressors.

Field Install Pump/Valve Relay Kit

The pump relay kit can be used to energize a supply pump or solenoid valve when there is a call for compressor operation. This relay can be used to switch either high or low voltage power.

Cupro-nickel Coil

A cupro-nickel heat exchanger is recommended in conditions anticipating moderate scale formation or in brackish water.

Horizontal (HZ) Unit - Field Convertible Discharge Air

All HZ units come standard with End Blow Discharge Air configuration. Straight Through Discharge Air can be easily field configured.



Warranty

Coverage for your Geothermal Heat Pump Limited Residential Warranty⁽¹⁾

With the limited residential warranty, you receive peace-of-mind knowing you will receive replacement parts protection for up to 10 years. This warranty offering covers all components incorporated into the unit cabinet at the time of manufacture, including a 10 year labor-allowance for defective components to help offset labor expenses if a component should fail. Other components or parts that are purchased from Bosch and installed in the field have a one year replacement parts limited warranty.



A Zero Energy
Capable Home
for Peace of Mind

The Bosch zero energy capable home is a full systems approach to creating a house that is not an energy drain on the planet's finite resources. This technology helps homeowners to reduce their monthly utility bills and protect the environment.

Bosch has assembled a comprehensive suite of heating, cooling, water heating, and energy-efficient appliances that, when installed in a home, reduces home energy usage due to intelligent product designs and higher efficiencies. In addition, this approach enables the homeowner to save enough power to offset the already reduced energy demand, meaning virtually a zero energy bill for the homeowner.

Ask your Bosch Contractor or go to Bosch-HomeComfort.us to learn more about how Bosch products can work together for your ultimate comfort.



System & Technical Information

Vertical





Vertical Cabinet BP Model Dimensions										
Model	Unit	Width (A)	Depth (B)	Height (C)						
012	in	21.75	21.75	32.75						
012	cm	55.25	55.25	83.19						
018	in	21.75	21.75	39.25						
010	cm	55.25	55.25	99.70						
024	in	21.75	26.25	47.25						
024	cm	55.25	66.68	120.02						
030	in	24.25	33.50	47.25						
030	cm	61.60	85.09	120.02						
036	in	24.25	33.50	47.25						
036	cm	61.60	85.09	120.02						
042	in	26.25	33.50	58.25						
042	cm	66.68	85.09	147.96						
048	in	26.25	33.50	58.25						
040	cm	66.68	85.09	147.96						

Horizontal Cabinet BP Model Dimensions										
Model	Unit	Width (A)	Depth (B)	Height (C)						
012	in	22.25	45.25	19.75						
012	cm	56.52	114.94	50.17						
018	in	26.26	45.25	19.75						
010	cm	66.70	114.94	50.17						
024	in	30.25	54.75	22.00						
024	cm	76.84	139.07	55.88						
030	in	30.25	68.25	22.00						
030	cm	76.84	173.36	55.88						
036	in	30.25	68.25	22.00						
036	cm	76.84	173.36	55.88						
042	in	30.25	79.00	22.00						
042	cm	76.84	200.66	55.88						
048	in	30.25	79.00	22.00						
048	cm	76.84	200.66	55.88						

ASHRAE / AHRI / ISO 13256-1. English (I-P) Units														
	Entering Water Temperatures													
	Water Loop (WLHP)			Ground Water (GWHP)			Ground Loop (GLHP)				Fluid	Air		
Model	Cooling 86°F		Heating 68°F		Coolng 59°F Heating 50°F		Cooling 77°F		Heating 32°F		Flow	Flow		
Number	Capacity and Efficiency Data												Rate	Rate
	Cooling Capacity (Btu/hr)	EER	Heating Capacity (Btu/hr)	СОР	Cooling Capacity (Btu/hr)	EER	Heating Capacity (Btu/hr)	СОР	Cooling Capacity (Btu/hr)	EER	Heating Capacity (Btu/hr)	СОР	(GPM)	(CFM)
	BP with PSC Motor													
BP012	12200	14.90	14600	5.00	14200	22.70	12000	4.30	12600	17.50	9300	3.60	4.0	400
	BP with ECM Motor (Constant Torque or Constant Air Flow)													
BP015	15200	17.50	17500	5.60	17000	28.80	13000	4.60	16200	20.60	11000	3.90	4.0	650
BP018 VT	19500	15.90	21300	5.00	21300	25.30	17700	4.40	20500	18.50	14800	3.70	5.0	650
BP018 HZ	19500	15.40	21300	5.00	21300	24.70	17700	4.40	20500	17.90	14800	3.65	5.0	650
BP024	24500	16.95	28500	5.15	28400	27.35	23700	4.50	26000	19.80	18000	3.70	6.0	850
BP030	27000	16.60	31000	5.70	31000	27.00	25000	4.95	28500	19.40	20300	3.95	7.0	1000
BP036 VT	36000	17.10	41000	5.50	40200	25.90	34400	4.90	37500	19.70	26000	3.90	10.0	1200
BP036 HZ	36000	16.10	41000	5.35	40200	24.30	34400	4.70	37500	18.70	26000	3.90	10.0	1200
BP042 VT	38400	15.20	42400	5.50	44100	25.60	35000	4.65	40600	19.40	26800	3.70	10.5	1400
BP042 HZ	38400	17.15	42400	5.80	44100	27.20	35000	5.00	40600	19.50	26800	4.00	10.5	1400
BP048 VT	44400	15.00	50000	5.25	51100	24.00	40500	4.30	46800	17.75	33400	3.70	12.0	1600
BP048 HZ	44400	15.00	50000	5.25	51100	24.00	40500	4.50	46800	17.80	33400	3.70	12.0	1600

About Bosch

Bosch Home Comfort Group in North America

Bosch Home Comfort Group is a leading source of high quality water heating and comfort systems. The company offers gas tankless, electric whole house and point-of-use water heaters, Bosch and Buderus floor-standing and wall mounted boilers, Bosch and FHP geothermal, water-source and air-source systems as well as controls and accessories for all product lines. Bosch Home Comfort is committed to being Simply Smart by offering products that work together as integrated systems that enhance quality of life in an ultra-efficient and environmentally friendly manner. For more information, visit bosch-homecomfort.us.

Bosch Group

The Bosch Group is a leading global supplier of technology and services in the areas of Automotive, Industrial Technology, Consumer Goods and Building Technology. The company was founded in Stuttgart, Germany, in 1886 and presently has more than 440 subsidiaries and is represented in over 150 countries.

In the U.S., Canada and Mexico, the Bosch Group manufactures and markets automotive original equipment and aftermarket solutions, industrial drives and control technology, power tools, security and communication systems, packaging technology, home comfort solutions, household appliances and software solutions. The Bosch Group's products and services are designed to improving quality of life by providing innovative and beneficial solutions. In this way, the company offers technology worldwide that is Invented for life. Additional information is available online at www.bosch.com



Bosch Home Comfort Group

Watertown, MA | Londonderry, NH | Ft. Lauderdale, FL

General Inquiries: 1-866-642-3198

Copyright © 2023 Bosch Home Comfort Group All rights reserved. Subject to change without notice.

76H991815H 5-23

www.bosch-homecomfort.us